



ecolf

0

We call it 'Non-Powered, Powered Access'

As part of the Eco range the EcoLift still harnesses the same Eco friendly revolutionary 'Patented Stored Power System' as the PecoLift but at 4.20 m offers almost a metre extra in working height.

With no batteries (to charge and look after) and no hydraulic oil, the EcoLift is truly an Eco friendly solution.

Typical applications and uses:

1st & 2nd Fix. Pipe Work, M & E. FM. Cleaning. Painting. Retail. Point of Sale. FM.

Key Features

- Intuitive to operate turn handle to elevate
- Patented* lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small foot print (1.28 m x 0.74 m)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operational costs, virtually maintenance free

PUSH AROUND - Self Powered Indoor Use

Working Height: 4.20 m

Applications: 1st & 2nd fix. Pipe Work, M&E. F.M. Cleaning. Painting. Point of Sale. Retail.






Specifications

WORKING DIMENSIONS

Maximum working height: Maximum platform height: Basket dimensions: Working foot print: Safe working load - platform: Maximum manual force: Maximum gradient for operation: Maximum wind force: Maximum castor point load: Maximum wheel force: Power Sound Level: 4.20 m 2.20 m 0.85 m (L) x 0.64 m (W) 1.28 m x 0.74 m 150 kg (1 person + tools) 200N 0.5 degrees Internal use only 0 m/s 155 kg (1.52kN) 155 kg (1.52kN) less then 70dBa

Safety features

- 'Auto-lok' brake on elevation
- Elevates only when operated
- Lifting mechanism interlocked



Unlimited



IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.



Z.A. du Parc Bonnel 102, rue de la Gaillette 59167 LALLAING

Bureau : 03.27.86.54.77 Portable : 06.80.67.33.39

www.sefomat.fr