

ECOLIFT WR

LOW-LEVEL ACCESS



PATENTED
STORED
POWER
SYSTEM



STANDARD SPECIFICATIONS

Performance

Maximum working height	4.20 m
Maximum platform height	2.20 m
Closed platform height	0.68 m
Working outreach	3 m
Basket dimensions	0.85 m (L) x 0.64 m (W)
Platform dimensions L x W	0.85m x 0.64m
Working foot print	1.28 m x 0.95 m
Safe working load - platform	150 kg (1 person + tools)
Safe working load - Standard tray	15 kg
Maximum manual force	200 N
Maximum gradient for operation	3°
Maximum wind force	Internal/external use 12.5 m/s
Maximum castor point load	165/1.62 (kg/kN)
Maximum wheel force	245 kg
Power Sound Level	less than 70DbA
Operating temperature (Max/Min)	50/ -18 °C

Closed dimensions

Length	1.28 m
Width	0.95 m
Height	1.95 m
Weight	358 kg

KEY SPECS

Platform carrying capacity: 150 kg
Dimension: 1.28 m x 0.70 m

Working Height: 4.20 m
Total Weight: 305 kg

KEY FEATURES

- Intuitive to operate - turn handle to elevate
- Patented* lift mechanism, no power required
- Lightweight, easy to maneuver
- Unlimited lift cycles, can be used 24/7
- Possibility to work indoor and outdoor
- Minimal operational costs, virtually maintenance free

STANDARD FEATURES

- Wind rated for outdoor use (12.5 m/s)
- Intuitive to operate – turn handle to elevate
- Patented lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small footprint (1.28 m x 0.95 m)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operating costs, virtually maintenance free
- Auto-lok brake on elevation
- Elevates only when operated
- Interlocked lifting mechanism
- Spirit Level
- Lanyard attachment
- Emergency lowering handle
- Forklift pockets
- Fold up step
- Rubber bump pads
- Lifting points
- Durable powder coated finish
- Anti-climb basket with removeable gates for emergency

ACCESSORIES & OPTIONS

- ATEX
- Tool Tethering options
- Steel tool tray

IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.

ECOLIFT WR

LOW-LEVEL ACCESS

OFFICIAL
distributor



ECOLIFT WR is the ultimate outdoor vertical platform lift, ideal for working at height. Its robust design ensures stability, durability and ease of use, even in difficult weather conditions. Its patented manual lifting mechanism eliminates the need for power sources, ensuring uninterrupted, environmentally-friendly operation.

Safety is a priority with the Ecolift WR, which features a stable base, non-slip platform and sturdy rails. Choose the Ecolift WR for unrivalled performance and reliability when working at height outdoors.

Invest in the Ecolift WR today to boost your productivity and ensure a safe and efficient working experience at height. Contact us to find out more about this revolutionary outdoor lifting platform.

Optional protective bellows on request



SEFOMAT

Z.A. du Parc Bonnel
102, rue de la Gaillette
59167 LALLAING

Office : (+33) 3.27.86.54.77
Mobile : (+33) 6.80.67.33.39

www.sefomat.fr  