

NANO 35

LOW-LEVEL ACCESS



STANDARD SPECIFICATIONS

Performance

Maximum working height	5.50 m
Maximum platform height	3.50 m
Closed platform height	0.70 m
Working outreach	1.00 m
Platform dimensions L x W	0.85 m x 0.72 m
Safe working load	200 kg (1 person + tools)
Maximum manual force	200N
Maximum wind force	Internal use only 0 m/s
Power sound level	less than 70 dBA

Closed dimensions

Length	1.20 m
Width	0.76 m
Height	1.95 m
Weight	432 kg

Battery charger specification

Input Voltage	110V - 230V
---------------	-------------

KEY SPECIFICATIONS

Platform carrying capacity:

200 kg

Dimension:

1.20 m x 0.76 m

Working Height:

5.50 m

Total Weight:

432 kg

KEY FEATURES

- ▀ The Nano 35 model is usually the first choice when a large working platform space is required on a small floor space
- ▀ Step height only 390 mm
- ▀ Only 1.20 m x 0.75 m working footprint
- ▀ Optimal width fits through single door openings
- ▀ Self-locking front wheels when raised
- ▀ Large platform, 0.85 m x 0.72 m, gives the operator more room to work

STANDARD FEATURES

- ▀ Low step height 390mm
- ▀ Footprint (1.2 m x 0.76 m)
- ▀ Optimal width to fit through single doorways
- ▀ Self locking fixed wheels when raised
- ▀ Large platform (0.85 m x 0.72 m)
- ▀ Simple push button controls from platform
- ▀ Quality steel construction and dual mast with ultra glide technology.
- ▀ Durable powder coated finish
- ▀ Fail safe hydraulic circuit
- ▀ Emergency lower from ground level
- ▀ Acoustic signal when lifting and lowering
- ▀ Spirit Level
- ▀ Battery charge indicator
- ▀ Lanyard attachment
- ▀ Forklift pockets
- ▀ Anti-climb basket with removable gates for emergency access

ACCESSORIES & OPTIONS

- ▀ Plug - 230V 2P EURO
- ▀ Plug - 110V 3P UK
- ▀ Plug - 230V 3P UK
- ▀ Plug - US STYLE for latin america
- ▀ Tool Tethering options
- ▀ Steel tool tray

IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.

NANO 35

LOW-LEVEL ACCESS

OFFICIAL
distributor



NANO 35 from Power Tower is an innovative solution designed to overcome challenges at height. With its exceptional features and cutting-edge technology, this electric aerial work platform is the ultimate answer to taking your work to new heights. Its electric mast, offering almost a metre more height than standard lifts like the Nano 25, makes it the perfect choice for those looking for a large platform in tight spaces.

The versatility of the Nano 35 means it can be used for a wide range of tasks, from facilities management to shop maintenance. Its compact design and manoeuvrability make it easy to transport and access tight spaces, making it the ideal solution for projects with limited access. Featuring a double mast and Ultra Glide technology, this platform ensures fast, effortless and safe lifting.



The Nano 35 work platform is much more than just an alternative to conventional scaffolding. Discover the power and precision of the Nano 35 to take your productivity to new heights.



**NEW
PRODUCT**

SEFOMAT

Z.A. du Parc Bonnel
102, rue de la Gaillette
59167 LALLAING

Office : (+33) 3.27.86.54.77
Mobile : (+33) 6.80.67.33.39

www.sefomat.fr  