



STANDARD SPECIFICATIONS

Performance

Maximum working height	3.50 m
Maximum platform height	1.50 m
Closed platform height	0.3 m
Platform dimensions L x W	0.72 m x 0.6 m
Working footprint	0.99 m x 0.70 m
Safe working load	150 kg (1 person + tools)
Maximum manual force	200 N
Maximum gradient for operation	0,5 °
Maximum wind force	Internal use only 0 m/s
Maximum castor point load	125/1.23 (kg/kN)
Maximum wheel force	125/1.23 (kg/kN)
Power Sound Level	less than 70 dBA

Closed dimensions

Length	0.99 m
Width	0.70 m
Height	1.55 m
Weight	196 kg

KEY SPECIFICATIONS

Platform carrying capacity:
150 kg

Dimension:
0.99 m x 0.70 m

Working Height:
3.50 m

Total Weight:
196 kg

KEY FEATURES

- Intuitive to operate - turn handle to elevate
- Patented lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small footprint (0.99 m x 0.70 m)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble-free service
- Minimal operational costs, virtually maintenance free

STANDARD FEATURES

- Intuitive to operate – turn handle to elevate
- Patented lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small footprint (0.99 m x 0.70 m)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operating costs, virtually maintenance free
- Auto-lok brake on elevation
- Auto-braked on entering basket
- Elevates only when operated
- Interlocked lifting mechanism
- Spirit Level
- Lanyard attachment
- Emergency lowering handle
- Forklift pockets
- Durable powder coated finish
- Anti-climb basket with removable gates for emergency

ACCESSORIES & OPTIONS

- ATEX
- Steel tool tray
- Transport Wheels
- Tool Tethering options

IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.

PECOLIFT

LOW-LEVEL ACCESS

OFFICIAL
distributor



PECOLIFT, leader in mobile platform lifts, simplifies access to elevated spaces, ideal for indoor environments. Lightweight and compact, it's easy to move around, suitable for warehouses, factories and building sites. As a replacement for ladders, it improves safety and ergonomics.

Featuring a patented manual lifting mechanism, the operator adjusts the height effortlessly by turning the handle. Eco-friendly, with no need for batteries or hydraulic oil, the Pecolift operates 24 hours a day, 7 days a week, with no cycle limits. It takes up very little space (0.99 m x 0.70 m) and weighs just 196 kg, so it won't damage floors and fits in standard doors and lifts.



This mobile lifting platform from Power Tower is designed to provide safe, ergonomic solutions for working at height. Using the Pecolift improves working conditions and increases productivity on industrial and other sites.



SEFOMAT

Z.A. du Parc Bonnel
102, rue de la Gaillette
59167 LALLAING

Office : (+33) 3.27.86.54.77
Mobile : (+33) 6.80.67.33.39

www.sefomat.fr  