

# POWER TOWER DUO

LOW-LEVEL ACCESS



## STANDARD SPECIFICATIONS

### Performance

Maximum working height	5.10 m
Maximum platform height	3.10 m
Closed platform height	0.74 m
Working outreach	1.0 m
Platform dimensions L x W	1.52 m x 0.75 m
Working foot print	1.89 m x 1.22 m
Safe working load	250 kg
Maximum manual force	200 N (1 person)/400 N (2 persons)
Maximum gradient for operation	0.5°
Maximum wind force	12.5 m/s

### Closed dimensions

Length	1.89 m
Width	0.78 m
Height	1.85 m
Weight	483 kg

### Power options

Battery	12V c/w automatic charger
Mains	110V or 230V
Controls	Simple push button basket controls.
Construction	Heavy duty fabricated steel superstructure, stainless steel bushed pivots, tough powder coated finish.
Safety	CE marked, complies with applicable European legislation including the Machinery Directive using the EN280 design standard. Full fail-safe hydraulics, automatic locking wheels.
Options	Pipe and board carrier kit

## STANDARD FEATURES

- Footprint (1.89 m x 1.22 m)
- Optimal width to fit through single doorways
- Large platform (1.52 m x 0.75 m)
- Simple push button controls from platform
- Quality steel construction
- Durable powder coated finish
- Fail safe hydraulic circuit
- Emergency lower from ground level
- Acoustic signal when lifting and lowering
- Auto-lock brake on elevation
- Spirit Level
- Battery charge indicator

## ACCESSORIES & OPTIONS

- Plug - 230V 2P EURO
- Plug - 110V 3P UK
- Plug - 230V 3P UK
- Plug - US STYLE for Latin America
- Tool Tethering options



## KEY SPECIFICATIONS

<b>Platform carrying capacity:</b> 250 kg	<b>Dimension:</b> 1.89 m x 0.78 m
<b>Working Height:</b> 5.10 m	<b>Total Weight:</b> 483 kg

## KEY SPECIFICATIONS

- Patented stabiliser deployment on elevation
- Capacity - 2 persons (indoors), 1 person (outdoors)
- 3.10 m platform height, 5.10 m working height
- 250 kg safe working load
- Compact - Only 0.78 m wide, passes easily through standard doorways
- Large 1.52 m x 0.75 m platform size
- 1.89 m x 1.22 m working footprint
- Easy access gate

### IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.

# POWER TOWER DUO

LOW-LEVEL ACCESS

OFFICIAL  
distributor



**Power Tower Duo** Power Tower offers efficient and safe access to elevated areas, making it a reliable industry benchmark. Designed for exceptional performance, it meets the needs of various sectors such as construction, facilities management and many others.

**The first two-person push tower,** it eliminates the need for additional tools or scaffolding, simplifying work processes, while its increased stability means that lifting accessories can be used for materials such as plasterboard and pipes.



**It brings significant value** in terms of productivity and safety, generating long-term savings. Distinctive features, such as the patented deployment of the stabilisers, make this aerial platform an essential choice for a variety of applications, from piping to painting. Explore the power and reliability of the Power Tower Duo to transform your operations and gain efficient access to elevated areas.



**SEFOMAT**

Z.A. du Parc Bonnel  
102, rue de la Gaillette  
59167 LALLAING

Office : (+33) 3.27.86.54.77  
Mobile : (+33) 6.80.67.33.39

[www.sefomat.fr](http://www.sefomat.fr)  